DOOH HAOSP01.8

PROFESSIONAL PLUG & PLAY DIGITAL-OUT-OF-HOME PRODUCTS







- Centralized content management and lower operational cost
- Limitless advertisement content management

1080x1920

- Turnkey solution for DOOH digital advertisement
- Customization for size, shape and color availability on request

BUS SHELTER ANKARA / TURKEY



Smoke

Monitoring

4

Temp

Monitoring

Slim

Front Access Lightweight

Voltage

Monitoring

General

Operating environment Pixel pitch Service type Calibrated brightness (nits) Lamp type Lifespan (hours at %50 brightness) White color calibration (adj.) Gray scale Brightness control Module Specifications Module dimensions (mm) Refresh frequency Module resolution LED drive method Module material PCB type PCB surface coating **Product Specifications** Optional double side Product material (housing) Product material (screen cover) Enclosure dimensions (mm) (width x height x depth) IP level Screen resolution Viewing angle (horizontal x vertical) Minimum viewing distance Operating temperature range Storage temperature range Operating humidity Power input voltage Power input frequency Active PFC I oad tolerance

outdoor 1.8mm front and rear access >3.650nits Flip-Chip Micro >100.000hours 3.500K~8.500K >16bits 256 level

> 160x180 3.840Hz 88x100 dynamic aluminum multilayer UV protected film

YES steel & aluminum without glass

1.315x2.782x255 IP65 600x1066px >160° x 160° >2m -15°C ~ +45°C

-20°C~+60°C 10% ~ 90% non-condensing 110~240 VAC 50~60Hz YES 25% min. Passive cooling without fan

Grey (RAL 7016)

Optional
Automatic & manual
Optional
YES
YES
YES
CAT or Fiber Optic
YES
Optional
YES
CE-EMC, CE-LVD, RoHS, FCC

YES

Options Internal player

Coolina

Other

Standard product color

Combined screen function

Brightness adjustment Dead pixel monitoring

Temperature monitoring Signal path backup Signal transmission Standby scheduling Power on/off scheduling Power saving mode Certification

Module monitoring

*The mechanical and electronic specification options are available.

Noiseless

D

Calibration

LEDECA

Fanless

-K Apron Teknoloji AS. reserves the right to change any product specification, discontinue of any product or services without prior notice

High Refresh

Rate

 $\cap C$

Easy To

Install

Wide Angle

Remote

Control