DOOH

DHAOSP02.9

PROFESSIONAL PLUG & PLAY
DIGITAL-OUT-OF-HOME PRODUCTS

Armour
LEDECA

1500x2500

1500x2500

- Centralized content management and lower operational cost
- Limitless advertisement content management
- Turnkey solution for DOOH digital advertisement
- Customization for size, shape and color availability on request

KADIKÖY
İSTANBUL / TÜRKİYE

General	
Operating environment	outdoor
Pixel pitch	2.9mm
Service type	front and rear access
Calibrated brightness (nits)	>4.500nits
Lamp type	SMD
Lifespan (hours at %50 brightness)	>100.000hours
White color calibration (adj.)	3.500K~8.500K
Gray scale	>14bits
Brightness control	256 level
Module Specifications	
Module dimensions (mm)	250x250
Refresh frequency	3.840Hz
Module resolution	86x86
LED drive method	dynamic
Module material	aluminum
PCB type	multilayer
PCB surface coating	humiseal
Product Specifications	
Optional double side	YES
Product material (housing)	steel & aluminum
Product material (screen cover)	without glass
Enclosure dimensions (mm) (width x height x depth)	1.732x3.360x255
IP level	IP65
Screen resolution	516x860px
Viewing angle (horizontal x vertical)	>120° x 120°
Minimum viewing distance	>3m
Operating temperature range	-15°C ~ +45°C
Storage temperature range	-20°C ~ +60°C
Operating humidity	10% ~ 90% non-condensing
Power input voltage	110 ~ 240 VAC
Power input frequency	50~60Hz
Active PFC	YES
Load tolerance	25% min.
Cooling	Passive cooling without fan
Standard product color	Grey (RAL 7016)
Other	
Combined screen function	Optional
Brightness adjustment	Automatic & manual
Dead pixel monitoring	Optional
Module monitoring	YES
Temperature monitoring	YES
Signal path backup	YES
Signal transmission	CAT or Fiber Optic
Standby scheduling	YES
Power on/off scheduling	Optional
Power saving mode	YES
Certification	CE-EMC, CE-LVD, RoHS, FCC
Options	
Internal player	YES

*Time synchronization is used to synchronize the time of contents on multiple DOOH.

*The mechanical and electronic specification options are available.

Front Access | Lightweight | Slim | Temp Monitoring | Smoke Monitoring | Voltage Monitoring | Remote Control | Easy To Install | Wide Angle | High Refresh Rate | Transparent | Noiseless | Calibration | Pixel Detection | Fanless

Apron Teknoloji AS. reserves the right to change any product specification, discontinue of any product or services without prior notice

TECHNICALSPECIFICATIONS

LEDECA