
CITYLINE AOSP02.9CL

OUTDOOR LED SCREENS FOR DIGITAL OUT-OF-HOME MESSAGING AT EXTREME ENVIRONMENTS



- Aluminum fanless design for high performance under extreme conditions
- Adjustable brightness optionally up to 10.000nits
- Lower power consumption with common-cathode technology
- Lightweight for easy adaptation and low cost framework design
- Production level calibration for best color uniformity

A1 TELECOM SHOP WIEN / AUSTRIA





General

Operating environment	outdoor
Pixel pitch	2.9mm
Service type	front and rear access
Calibrated brightness (nits)	5.000nits
Lamp type	SMD
Lifespan (hours at %50 brightness)	>100.000hours
White color calibration (adj.)	3.500K~8.500K
Gray scale	>16bits
·	256 level
Brightness control	230 level
Module Specifications	500 350
Module dimensions (mm)	500x250
Refresh frequency	2.880Hz - 3.840Hz
Module resolution	172x86px
LED drive method	dynamic
Module material	aluminum
Module type	sealed
PCB type	multilayer
PCB surface coating	humiseal
Panel Specifications	
Panel material	aluminum
Panel paint	ES powder coated
Panel dimensions (mm) ¹	500x1.000
	86mm
Panel depth	
IP level	IP67 front, IP65 rear
Panel weight	<16kg
Panel resolution	172x344px
Pixel density (pcs/sqm)	118.336
Viewing angle (horizontal x vertical)	>160° x 140°
Minimum viewing distance	>3m
Operating temperature range	-20°C ~ +60°C
Storage temperature range	-25°C ~ +60°C
Operating humidity	10% ~ 90% non-condensing
Power input voltage	110 ~ 240 VAC
Power input frequency	50~60Hz
Average power per sqm	<140W
Max power per sqm	<650W
Active PFC	YES
Load tolerance ²	25% min.
Panel installation type	Fixed installation
Cooling	Passive cooling without fan
Other	
Max input resolution	FHD, UHD, 4K, 8K
Standard video sources ³	All digital formats
Brightness adjustment	Automatic & manual
Death pixel monitoring	Optional
Module monitoring	YES
Temperature monitoring	YES
Smoke monitoring	Optional
Voltage monitoring	YES
Power redundancy	N/A
Signal path backup	YES
Signal transmission	CAT or Fiber Optic
Standby scheduling	YES
Power on/off scheduling	Optional
Power saving mode	YES
Certification	CE-EMC, CE-LVD, RoHS, FCC
Options	
Energy-friendly (Avarage/max	7011/25011
power per sqm)	70W/350W
Higher Brightness - CLX	6.500nits
Corner installation	90-degree / curved

- **1-** Panel dimensions can change upon customer request
- 2- That value is the remain capacity of PSU's at 100% brightness and white color content
- 3- Different types of video input available as option





















High Refresh



































Noiseless



Pixel