

# STAGE LDCISP03.9ST

LED SCREENS FOR STAGE,  
EVENT AND RENTAL  
INDUSTRIES



- Quick maintenance within 20 seconds
- One man installation with magnet on top panel design
- Aluminum structure with passive cooling and fanless design
- Reinforced module structure suitable for continuous disassembly and installation
- Production level calibration for best color uniformity
- All models have 500x500mm panel options
- Strong structure supporting +10 and -10 degree curving
- 45 degree Cut Corner panel for all pixel pitches
- Creative design installation

## INDOOR EVENT ISTANBUL / TURKEY



### General

Operating environment	indoor
Pixel pitch	3.9mm
Service type	rear access
Calibrated brightness (nits)	600nits
Lamp type	SMD
Lifespan (hours at %50 brightness)	>100.000hours
White color calibration (adj.)	3.500K~8.500K
Gray scale	>16bits
Brightness control	256 level

### Module Specifications

Module dimensions (mm)	250x250
Refresh frequency	3.840Hz
Module resolution	64x64px
LED drive method	dynamic
Module material	plastic (PC)
Module type	sealed
PCB type	multilayer
PCB surface coating	humiseal

### Panel Specifications

Panel material	die-casting aluminum
Panel paint	ES powder coated
Panel dimensions 'mm'	500x1.000
IP level	IP22 front and rear
Panel weight	<15kg
Panel resolution	128x256px
Pixel density (pcs/sqm)	65.536
Viewing angle (horizontal x vertical)	>120° x 120°
Minimum viewing distance	>4m
Operating temperature range	0°C ~ +50°C
Storage temperature range	-20°C ~ +60°C
Operating humidity	10% ~ 90% non-condensing
Power input voltage	110 ~ 240 VAC
Power input frequency	50 ~ 60 Hz
Average power per sqm	<120W
Max power per sqm	<600W
Active PFC	YES
Load tolerance <sup>2</sup>	25% min.
Panel installation type	Rental type
Cooling	Passive cooling
Other	

### Max input resolution

Standard video sources <sup>3</sup>	All digital formats
Brightness adjustment	Automatic & manual
Death pixel monitoring	Optional
Module monitoring	YES
Temperature monitoring	YES
Smoke monitoring	Optional
Voltage monitoring	YES
Power redundancy	N/A
Signal path backup	YES
Signal transmission	CAT or Fiber Optic
Standby scheduling	YES
Power on/off scheduling	Optional
Power saving mode	YES
Certification	CE-EMC, CE-LVD, RoHS, FCC

### Options

\*The mechanical and electronic specification options are available.

- Panel dimensions can change upon customer request
- That value is the remain capacity of PSU's at 100% brightness and white color content
- Different types of video input available as option



Apron Teknoloji AS. reserves the right to change any product specification, discontinue of any product or services without prior notice